



Electronic temperature indicator battery powered **GPA100**

- Analog input for RTD Pt100 or Pt1000, 2-wire
- Stainless steel case
- 3 membrane buttons for configuration and operation
- Battery powered 2x1,5V DC
- min. and max. memory
- Automatic switch-off

CE

Technical Specifications

Application

- Local temperature indication from RTD sensors Pt100 or Pt1000

Technical characteristics

- User friendly configuration via membrane buttons
- Energy saver function - automatic switch-off after configurated period (max. 100min)
- Memory for min. and max. value (peak reading pointer function)
- Alarm visualisation on display min. and max. limit value

Installation

- Mounting on wall bracket with the possibility of cable sensor connection
- Direct mounting on the sensor (instead of the connection head)

Measuring input	Pt100 or Pt1000 2-wire
Measuring range	-50...+600°C
Accuracy	≤ 0.3% of range
Display	4 digits, 18mm high, LCD
Resolution	0.1°C or 1°C, configurable
Functions.....	On/Off, °C/°F/ K, min/max, auto off (in range up 100min)
Buttons	3 membrane buttons for configuration and operation
User calibration	via buttons
Alarms	2 limit alarms
Supply	2 batteries 1.5V, size AA
Temperatura otoczenia	-10...+50°C
Humidity	0...85% RH
Case diameter	100mm
Case material	stainless steel
IP protection	IP65
Weight.....	approx. 700g without batteries

Visit us online at: www.guenther.eu

Guenther Polska Sp. z o.o.

Wrocławska 27C Tel. +48 (0) 71 352 70 70
55-095 Długołęka Fax +48 (0) 71 352 70 71

E-Mail biuro@guenther.com.pl
Internet www.guenther.com.pl